

HPS 500 Series Data Sheet

Dimensions -S- Housing	21-1/4" x 13-1/4" x 13-1/4"
Duct Connections	8" Dia. Inlet / 6" Dia. Outlet
Portable	12" x 12" Inlet / 6" Dia. Outlet with Guard
Completed Weight	36 Lbs.
Motor/Blower Type	Forward Curved Centrifugal
Max Amps @ 120V	5
Hz	60
Phase	Single
Circuit	15 Amp
Running Amps With New Filters	25% @ 2.09 / 50% @ 2.92 75% @ 2.97 / 100%
dB Level without Ducting	25% @ 58dB / 50% @ 70.8dB 75% @ 73.6dB / 100% @ 73.7dB
CFM After Filters	500
Pre-filter	Dual Layer
Carbon Filter Pad	Up To 1 Lbs. Activated
HEPA	Certified H14 99.995% @ MPPS
On/Off	Sealed Lighted Rocker Switch

Optional OA System

The "S" OA systems have 1 activated Carbon "OA Cartridge" in place of the HEPA filter. (up to 5 Lbs.)

www.pureairsystems.com

[1-800-869-8025](tel:1-800-869-8025)

[Email: info@pureairsystems.com](mailto:info@pureairsystems.com)

[3079 N County Rd. 200 W., Danville, IN 46122](http://3079%20N%20County%20Rd.%20200%20W.,%20Danville,%20IN%2046122)

